



19 June 2023

MICROFLOOR Gloss 4370

Commercial-In-Confidence Statement of VOC in Coating

The method for the determination of VOC levels of the listed products is detailed in
South Coast Air Quality Management District (California, U.S.) –
Rule 1136 (Wood Products Coatings)

Product	Description	VOC Content
4370	MICROFLOOR Gloss	94 g/L

Note: The VOC levels have been determined by the calculation method. The information used is based on supplier information (e.g. SDS and Datasheet) for the ingredients and our own formulation of the coating. The VOC content above is the maximum VOC exclusive of water and exempt compounds.



This declaration is provided in good faith and the information contained herein is based on data considered accurate at the time of preparing this document. No warranty is expressed or implied regarding the accuracy of this data. This declaration is not intended in any way to be a warranty of performance or compliance to any specification, expressed or implied.

■ **NEW SOUTH WALES**
8/26 Nelson Road, Yennora NSW 2161
PO Box 310, Fairfield NSW 1860
Ph: +61 2 9795 3700
Free Call: 1300 132 202

mirotone.com
@MirotoneANZ

■ **VICTORIA**
147 Ordish Road, Dandenong
VIC 3175
Ph: +61 2 9795 3700
Free Call: 1300 132 202

polycure.com.au
@Polycure

■ **QUEENSLAND**
679 Progress Road, Wacol QLD 4076
PO Box 3941, Mt Ommaney QLD 4074
Ph: +61 2 9795 3700
Free Call: 1300 132 202

qtf.com.au
@QuantumTimberFinishes_ANZ

■ **WESTERN AUSTRALIA**
100 Mulgul Road, Malaga WA 6090
Ph: +61 2 9795 3700
Free Call: 1300 132 202

